



Fig.1




Fig.2





Fig.3




Q

テーパ	Code No.	ドッキング 径Q	L	C	C ₁	H	H ₁	接続ボルト No.	Fig.	重量 (kg)	
NC5- 46	NC5- 46-Q26- 40	26	40	50	45	18	6	B26N	3	0.4	
	NC5- 63-Q 9- 80, 95	9	80, 95	19	30	48, 63	5, 27	B19	2	1.6, 1.7	
NC5- 63	-Q12- 80, 110	12	80, 110	24	35	48, 78	12, 50	B12		1.6, 1.7	
	-Q16- 95, 125	16	95, 125	31	42	63, 93	22, 55	B16		1.9, 2.1	
	-Q20- 80, 110	20	80, 110	40	50	48, 78	27, 60	B20		2.0, 2.2	
	-Q26- 50, 95, 140	26	50, 95, 140	50	—	20, 65, 110	—	B26N		1	0.9, 1.5, 2.3
	-Q34- 95, 110	34	95, 110	64	62	68, 83	55, 70	B34			3.0, 3.4
	-Q42- 95	42	95	83	62	68	55	B42			3.6
NC5- 85	NC5- 85-Q 9-110, 125	9	110, 125	19	40	72, 87	5, 27	B19	2	2.9, 3.1	
	-Q12- 95, 125	12	95, 125	24	44	57, 87	12, 50	B12		2.5, 3.2	
	-Q16-125, 155	16	125, 155	31	50	87, 117	22, 55	B16		3.6, 3.8	
	-Q20-110, 125	20	110, 125	40	60	72, 87	27, 60	B20		3.7, 3.8	
	-Q26- 65, 140, 170	26	65, 140, 170	50	65	27, 102, 132	—, 40, 110	B26N	1, 2, 2	2.5, 4.6, 4.7	
	-Q34-140, 170, 200	34	140, 170, 200	64	80	102, 137, 167	—, 117, 147	B34		4.5, 6.4, 6.8	
	-Q42-125, 190	42	125, 190	83	—	87, 152	—	B42		8.0	
NC5-100	NC5-100-Q 9-110, 125	9	110, 125	19	40	67, 82	5, 27	B19	2	4.0, 4.2	
	-Q12- 95, 125	12	95, 125	24	44	52, 82	12, 50	B12		4.1, 4.3	
	-Q16-125, 155	16	125, 155	31	50	82, 112	22, 55	B16		4.7, 4.9	
	-Q20-110, 125	20	110, 125	40	60	67, 82	27, 60	B20		4.8, 4.9	
	-Q26- 65, 140, 170	26	65, 140, 170	50	65	27, 97, 127	—, 45, 110	B26N	1, 2, 2	3.6, 5.7, 5.8	
	-Q34-140, 170, 200	34	140, 170, 200	64	80	97, 127, 157	—, 117, 147	B34		5.6, 7.5, 7.9	
	-Q42-125, 190	42	125, 190	83	—	87, 152	—	B42		9.1	

★全シリーズスルーホール付きです。

★接続ボルト及びレンチは付属しています。

★標準よりL寸法が長い場合、有効ボーリング長MとQ No.をご指定下さい。



NC5